



REVISION		RECORD	
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:
 Pitch: 9.5mm
 Rated Voltage: 300V
 Rated Current: 20A
 Withstand Voltage:
 AC2500V for 1 minute
 Insulation Resistance:
 1000MΩ / DC500V
 Using Temperature Range:
 -40°C ~ +130°C
 Wire range: 22~12 AWG
 Screw Torque Value: 1.2Nm

技术要求:
 间距: 9.5mm
 额定电压: 300V
 额定电流: 20A
 耐电压值: AC2500V/min
 绝缘阻抗: 1000MΩ / DC500V
 使用条件: -40°C~+130°C
 适用线规: 22~12 AWG
 螺丝扭矩: 1.2Nm

	Pitch dimension			Nominal dimension					—
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		∇
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

4	LW-圆柱	5034A0Y01AV	P	PA66	
3	LW1Q-9.5-焊脚	5002B0003AV	P	黄铜	镀锡
2	M4*8-7.5*7.5	SQFFA408041V	P	碳钢	三价铬钝化彩锌
1	LW1M-9.5-本体	5002M0YXXAV	1	PBT	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	ZGC	DATE 2020/08/26	UNITS MM	THIRD ANGLE PROJECTION	SHEET
CHK.	DATE		SIZE A4		1 of 1
APP.	DATE		SCALE 1:1	DWG NO. SP-2-5002017	REV: V0
上海有乐电气有限公司 Shanghai YouLe Electric CO.,LTD				TITLE	LW1MQJ-9.5-XP-1Y-00A LW1MQJ-9.5-成品